

TOPLO VALJANO

Premer: od 20 do 120 mm
 Dolžina palic: Cca. 4 – 6 m
 Toleranca: EN 10059 (DIN 1014)
 Certifikat: EN 10204/3.1

SVETLO VLEČENO

Premer: od 5 do 60 mm
 Dolžina palic: Cca. 3 – 4 m
 Toleranca: EN 10278 (DIN 178)
 Certifikat: EN 10204/3.1



HOT ROLED

Dimensions: from 20 to 120 mm
 Bar length: Cca. 4 – 6 m
 Tolerance: EN 10059 (DIN 1014)
 Certificate: EN 10204/3.1

COLD DRAWN

Dimensions: from 5 to 60 mm
 Bar length: Cca. 3 - 4 m
 Tolerance: EN 10278 (DIN 178)
 Certificate: EN 10204/3.1

DIMENZIJE	KG/M
DIMENSIONS	KG/M
4	0,12
5	0,23
6	0,28
7	0,39
8	0,50
9	0,64
10	0,79
11	0,95
12	1,13
13	1,33
14	1,54
15	1,77
16	2,01
17	2,27
18	2,54
19	2,8
20	3,14
21	3,46
22	3,80
23	4,15
24	4,52
25	4,91
26	5,31
27	5,72
28	6,15
29	6,60
30	7,07
32	8,04

DIMENZIJE	KG/M
DIMENSIONS	KG/M
34	9,08
35	10,17
38	11,34
40	12,56
42	13,85
44	15,20
45	15,90
46	16,61
48	18,09
50	19,63
52	21,23
54	22,89
55	23,48
56	24,62
58	26,41
60	28,26
62	30,17
64	32,15
65	33,16
66	34,20
68	36,30
70	38,47
72	40,69
74	42,99
75	44,13
76	45,34
78	47,76
80	50,24

DIMENZIJE	KG/M
DIMENSIONS	KG/M
100	78,50
105	86,55
110	94,99
115	103,82
120	113,04