


TOPLO VALJANO , LUŽENO

Dolžina palic: Cca. 6 m
Toleranca: EN 10279/10365
Certifikat: EN 10204/3.1



HOT ROLED , PICKLED

Bar length: Cca. 6 m
Tolerance: EN 10279/10365
Certificate: EN 10204/3.1



DIMENZIJA - SIZES

	B		H		S ₁		S ₂	Kg/m
U 20	20	x	10	x	3	x	3,5	0,86
U 30	30	x	15	x	3	x	3,5	1,37
				x	4	x	4,5	1,78
			33	x	5	x	7	4,3
U 40	40	x	20	x	3	x	3,5	1,8
				x	4	x	4,5	2,4
		x	35	x	5	x	7	4,8
U 50	50	x	25	x	3	x	3,5	2,28
				x	5	x	5	3,6
						x	6	4,2
				x	6	x	6	4,1
		x	38	x	5	x	7	5,7
U 60	60	x	30	x	5	x	5	4,37
				x	6	x	6	5,1
U 65	65	x	42	x	5,5	x	7,5	7,4
U 80	80	x	40	x	4	x	4	4,9
				x	5	x	5	5,94
				x	6	x	6	7
		x	45	x	6	x	6	7,6
						x	8	8,64
U 100	100	x	50	x	4	x	4	6,2
				x	5	x	5	7,65
				x	6	x	6	8,94
						x	8,5	10,6
U 120	120	x	55	x	7	x	9	13,5
		x	60	x	5	x	5	9,2
				x	6	x	6	10,93
U 130	130	x	65	x	6	x	6	12,08
U 140	140	x	60	x	7	x	10	16,4
		x	70	x	7	x	7	14,62
U 150	150	x	75	x	6	x	6	13,8
U 160	160	x	65	x	7,5	x	10,5	18,8
		x	80	x	8	x	8	19,21
U 180	180	x	70	x	8	x	11	22
				x	9	x	12	24,2
U 200	200	x	75	x	8,5	x	11,5	25,3
				x	10	x	13	29,52
		x	100	x	6	x	6	18,7
				x	8	x	8	24,6
				x	10	x	10	30,4
U 220	220	x	80	x	9	x	12,5	29,4
				x	10	x	13	31,8
U 240	240	x	85	x	9,5	x	13	33,2
U 300	300	x	100	x	10	x	16	46,45


TOPLO VALJANO , LUŽENO

Dolžina palic: Cca. 6 m
Toleranca: EN 10279/10365
Certifikat: EN 10204/3.1



HOT ROLED , PICKLED

Bar length: Cca. 6 m
Tolerance: EN 10279/10365
Certificate: EN 10204/3.1




	DIMENZIJA - SIZES								Kg/m
	A		B		S ₁		S ₂		
IPE 80	80	x	46	x	3,8	x	5,2	6,1	
IPE 100	100	x	55	x	4,1	x	5,7	8,1	
IPE 120	120	x	64	x	4,4	x	6,3	10,4	
IPE 140	140	x	73	x	4,7	x	6,9	12,9	
IPE 160	160	x	82	x	5	x	7,4	15,8	
IPE 180	180	x	91	x	5,3	x	8	18,8	
IPE 200	200	x	100	x	5,6	x	8,5	22,4	
IPE 220	220	x	110	x	5,9	x	9,2	25,2	
IPE 240	240	x	120	x	6,2	x	9,8	29,4	
IPE 270	270	x	135	x	6,6	x	10,2	35,2	
IPE 300	300	x	150	x	7,1	x	10,7	41,4	
IPE 330	330	x	160	x	7,5	x	11,5	47,3	
IPE 360	360	x	170	x	8	x	12,7	56	
IPE 400	400	x	180	x	8,6	x	13,5	63,6	

TOPLO VALJANO , LUŽENO


Dolžina palic: Cca. 6 m
 Toleranca: EN 10279/10365
 Certifikat: EN 10204/3.1


HOT ROLED , PICKLED

Bar length: Cca. 6 m
 Tolerance: EN 10279/10365
 Certificate: EN 10204/3.1


DIMENZIJA - SIZES
Kg/m

	A		B		S₁		S₂		
HEB 100	100	x	100	x	6	x	10		20,4
HEB 120	120	x	120	x	6,5	x	11		26,7
HEB 140	140	x	140	x	7	x	12		33,7
HEB 160	160	x	160	x	8	x	13		42,6
HEB 180	180	x	180	x	8,5	x	14		51,2
HEB 200	200	x	200	x	9	x	15		61,3
HEB 220	220	x	220	x	9,5	x	16		71,5
HEB 240	240	x	240	x	10	x	17		83,2
HEB 260	260	x	260	x	10	x	17,5		93
HEB 280	280	x	280	x	10,5	x	18		103
HEB 300	300	x	300	x	11	x	19		117

H-PROFILI, lahki
H - BEAMS, light

DIMENZIJA - SIZES
Kg/m

	A		B		S₁		S₂		
HEA 100	96	x	100	x	5	x	8		16,7
HEA 120	114	x	120	x	5	x	8		19,9
HEA 140	133	x	140	x	5,5	x	8,5		24,7
HEA 160	152	x	160	x	6	x	9		30,4
HEA 180	171	x	180	x	6	x	9,5		35,5
HEA 200	190	x	200	x	6,5	x	10		42,3
HEA 220	210	x	220	x	7	x	10		48,6
HEA 240	230	x	240	x	7,5	x	12		58,5
HEA 260	250	x	260	x	7,5	x	12,5		63,6
HEA 280	270	x	280	x	8	x	13		72,9
HEA 300	290	x	300	x	8,5	x	13,5		80,4


TOPLO VALJANO , LUŽENO

Dolžina palic: Cca. 6 m
Toleranca: EN 1055
Certifikat: EN 10204/3.1



HOT ROLED , PICKLED

Bar length: Cca. 6 m
Tolerance: EN 1055
Certificate: EN 10204/3.1



DIMENZIJA - SIZES

Kg/m

	B		A		S	
T 20	20	x	20	x	3	0,88
				x	4	1,15
T 25	25	x	25	x	3	1,13
				x	3,5	1,31
				x	4	1,5
T 30	30	x	30	x	3	1,36
				x	4	1,77
T 35	35	x	35	x	4	2,1
T 40	40	x	40	x	3	1,85
				x	4	2,5
				x	5	2,96
T 45	45	x	45	x	5,5	3,67
T 50	50	x	50	x	3	2,3
				x	4	3,1
				x	5	3,8
				x	6	4,5
T 60	60	x	60	x	3	2,8
				x	4	3,7
				x	5	4,6
				x	6	5,5
T 70	70	x	70	x	7	7,3
T 80	80	x	80	x	8	9,7
T 90	90	x	90	x	9	12,5
T 100	100	x	100	x	8	12,4
				x	10	15,1
T 120	120	x	120	x	13	23,7
T 140	140	x	140	x	15	31,8
TB 20	20	x	40	x	4	1,79
TB 25	25	x	50	x	5	2,76
TB 30	30	x	60	x	5,5	3,7
TB 35	35	x	70	x	6	4,7
TB 40	40	x	60	x	4	3,2
		x	80	x	7	6,2
TB 50	50	x	100	x	8,5	9,5
TB 60	60	x	120	x	10	13,4