


IZTISNJENE PALICE T66

Dolžina palic: 6 m


Certifikat: EN 10204/3.1



EXTRUDED T66

Lenght: 6 m

Certificate: EN 10204/3.1



PREMER V MM

DEBELINA V MM - TICHNESS IN MM

Diameter in mm	1	1,5	2	2,5	3	4	5	10	15
6	0,042								
8	0,059								
10	0,076		0,136						
12	0,093	0,134	0,170						
13	0,102	0,146							
14	0,110	0,159	0,203						
15	0,119	0,172	0,225						
16	0,127	0,184	0,237	0,286					
18		0,210	0,271						
20	0,161	0,235	0,305		0,432		0,636		
22		0,261	0,339						
25	0,203	0,300	0,390	0,477	0,560		0,848		
28		0,337	0,441		0,636				
30		0,369	0,475	0,583	0,687	0,881	1,060		
32		0,387	0,509						
35		0,426	0,560	0,689	0,814	1,051	1,270		
38			0,610		0,890	1,153			
40		0,490	0,644	0,795	0,940	1,220	1,484		
42			0,678		0,990	1,289			
45		0,553	0,730	0,901	1,070		1,700		
48		0,591	0,780		1,140	1,490			
50	0,415	0,617	0,814	1,010	1,195	1,560	1,910	3,393	
55			0,899						
60		0,744	0,983	1,220	1,450	1,899	2,330	4,240	5,723
65			1,070				2,543		

PREMER V MM	DEBELINA V MM - THICKNESS IN MM								
Diameter in mm	1	1,5	2	2,5	3	4	5	10	15
70			1,153	1,537	1,704	2,238	2,755	5,087	
75				1,537			2,967		
76					1,857				
80			1,323	1,643	1,958	2,580	3,180	5,934	
90			1,492		2,213	2,916	3,603	6,782	
100			1,662		2,467	3,256	4,027	7,630	
108					2,671				
110		1,380					4,451		
120					2,977	3,934	4,875	9,326	
125						4,103			
130							5,299		
140						4,612	5,723	11,021	
150					3,740		6,150	11,869	
160							6,570		
180							7,418		
200							8,270		
250							10,386		